

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

B96

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G02F 1/167, 1/133	A2	(11) International Publication Number: WO 98/19208 (43) International Publication Date: 7 May 1998 (07.05.98)
<p>(21) International Application Number: PCT/US97/18643</p> <p>(22) International Filing Date: 17 October 1997 (17.10.97)</p> <p>(30) Priority Data: 08/738,260 25 October 1996 (25.10.96) US</p> <p>(71) Applicant: MASSACHUSETTS INSTITUTE OF TECHNOLOGY - GGY- [US/US]; 77 Massachusetts Avenue, Cambridge, MA 02139 (US).</p> <p>(72) Inventors: JACOBSON, Joseph, M.; Apartment 1, 31 Linnaean Street, Cambridge, MA 02138 (US). COMISKEY, Barrett; 50 Massachusetts Avenue, Cambridge, MA 02139 (US).</p> <p>(74) Agents: FRANK, Steven, J. et al.; Cesari and McKenna, LLP, 30 Rowes Wharf, Boston, MA 02110 (US).</p>		<p>(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, HU, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU. ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NI, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>
<p>(54) Title: NONEMISSIVE DISPLAYS AND PIEZOELECTRIC POWER SUPPLIES THEREFOR</p>		
<p>(57) Abstract</p> <p>An electrophoretic display has a substantially two-dimensional arrangement of microcapsules each having therein an electrophoretic composition of a dielectric fluid and a suspension of particles that visually contrast with the dielectric liquid and also exhibit surface charges; a pair of electrodes, at least one of which is visually transparent, disposed on and covering opposite sides of the microcapsule arrangement; and means for creating a potential difference between the two electrodes, the potential difference causing the particles to migrate toward one of the electrodes. The display may be powered by one or more piezoelectric elements, which are also suitable for powering other types of nonemissive displays.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

NONEMISSIVE DISPLAYS AND PIEZOELECTRIC POWER SUPPLIES THEREFOR

5

FIELD OF THE INVENTION

The present invention relates to electronic display elements, and more particularly to nonemissive displays.

10

BACKGROUND OF THE INVENTION

Nonemissive displays convey information using contrast differences, which are achieved by varying the reflectance of different frequencies of light; they are thus distinct from traditional emissive displays, which stimulate the eye by emitting light. One type of nonemissive display is an electrophoretic display, which utilizes the phenomenon of electrophoresis to achieve contrast. Electrophoresis refers to movement of charged particles in an applied electric field. When electrophoresis occurs in a liquid, the particles move with a velocity determined primarily by the viscous drag experienced by the particles, their charge, the dielectric properties of the liquid, and the magnitude of the applied field.

An electrophoretic display utilizes charged particles of one color suspended in a dielectric liquid medium of a different color (that is, light reflected by the particles) is absorbed by the liquid. The suspension is housed in a cell located between (or partly defined by) a pair of oppositely disposed electrodes, one of which is transparent. When the electrodes are operated to apply a DC or pulsed field across the medium, the particles migrate toward the electrode of opposite sign. The result is a visually observable color change. In particular, when a sufficient number of the

particles reach the transparent electrode, their color dominates the display; if the particles are drawn to the other electrode, however, they are obscured by the color of the liquid medium, which dominates instead.

5 Ideally, the particles maintain a strong uniform charge throughout the lifetime of the device and move as rapidly as possible under the influence of a relatively small electric field. The switching time of suspended particles located between two electrodes is given by

$$10 \quad t = \frac{6\pi d^2 \eta}{V \epsilon \zeta}$$

where d is the spacing between electrodes, η is the viscosity of the liquid medium, ϵ is its dielectric constant, V is the potential difference between the electrodes, and ζ is the zeta potential of the particles. The quantity t represents the "switching time," i.e., the time required for the population of particles to migrate from one of the electrodes to the other. Thus, the system is usually selected to minimize t . For example, the spacing between electrodes is as small as is necessary to ensure that the particles are completely obscured following migration away from the transparent electrode.

Useful electrophoretic displays are bistable: their state persists even after the activating electric field is removed. This is generally achieved via residual charge on the electrodes and van der Waals interactions between the particles and the walls of the electrophoretic cell. Unfortunately, the stability of current electrophoretic displays is limited. Although flocculation or settling of particles can be avoided by matching the density of the particles with that of the liquid medium, long-term particle agglomeration remains a problem. That is, cohesive forces among particles may eventually overcome dispersive forces,

-3-

degrading the appearance and function of the display. For example, particle agglomerations respond less efficiently to an applied field (increasing switching time) and are also more vulnerable to the action of gravity (limiting usefulness in arbitrary orientations); thus, if the display is oriented vertically, gravity can overcome adhesion to the cell wall and cause agglomerations to settle.

DESCRIPTION OF THE INVENTION

Brief Summary of the Invention

10 In accordance with the invention, the foregoing limitations are overcome by microencapsulating individual elements of an electrophoretic display. This approach eliminates the effects of agglomeration on a scale larger than the size of the capsule, which preferably is sufficiently
15 small to be individually unnoticeable. Thus, the capsules function in a manner similar to pixels (although typically they are not individually addressable); even if agglomeration occurs, its effect is confined to a very small area. Furthermore, by setting an upper limit to the possible size of
20 an agglomeration—that is, by preventing accumulations larger than the particle content of a capsule—the bulk effects of diminished field responsiveness and vulnerability to gravity are likewise limited.

Although, again, individual capsules within a display
25 element are typically not individually addressed, the approach of the invention lends itself to production of relatively small multiple-capsule elements that can themselves be individually addressable components of a larger array. For example, the elements can each present a circular profile and
30 be arrayed as a matrix, functioning as pixels in an alphanumeric display.

-4-

Accordingly, in a first aspect, the invention comprises an electrophoretic display having a substantially two-dimensional arrangement of microscopic containers ("microcapsules"), each microcapsule having therein an electrophoretic composition of a dielectric fluid and a suspension of particles that visually contrast with the dielectric liquid and also exhibit surface charges; a pair of electrodes, at least one of which is visually transparent, disposed on and covering opposite sides of the microcapsule arrangement; and means for creating a potential difference between the two electrodes, the potential difference causing the particles to migrate toward one of the electrodes. The microcapsule arrangement can be flat or curved; as used herein, the term "two-dimensional" refers to arrangements that may be fully planar, distorted or curved, and does not exclude some three-dimensional thickness. The arrangement can involve packing the microcapsules against one another in an array (generally one microcapsule thick), dispersing the microcapsules in a transparent matrix, or forming cavities or voids within such a matrix that themselves constitute the microcapsules.

In a second aspect, the invention provides novel means of electrically powering nonemissive displays using one or more piezoelectric elements (such as a sheet of polyvinylidene fluoride). Generally, the invention in this aspect may comprise a pair of oppositely disposed electrodes and, located therebetween, at least one display element, the display element being visually responsive to a potential difference between the electrodes; and a piezoelectric element connected to the electrodes, deformation of the piezoelectric element

Brief Description of the Drawings

The foregoing discussion will be understood more readily from the following detailed description of the invention, when taken in conjunction with the accompanying drawings, in which:

5 FIGS. 1A-1B are enlarged sectional views showing
microencapsulated electrophoretic display arrangements in
accordance with the present invention;

10 FIGS. 2A and 2B schematically illustrate piezoelectric
driver circuitry useful for operating nonemissive
displays including (but not limited to) those depicted in
FIGS. 1A-1B;

FIG. 3 is a schematic elevation of a specific application
of the invention in a footwear environment;

15 FIG. 4A is a schematic elevation of another footwear
application;

FIG. 4B schematically illustrates representative
circuitry for implementing the application shown in FIG.
4A;

20 FIG. 5 is a partially schematic isometric view of a
specific application of the invention in a paper
publication environment;

FIG. 6 is a partially schematic isometric view of the
invention implemented in an acoustically coupled mode;

25 FIG. 7A is a partly schematic plan view of a specific
application of the invention in a wristwatch environment;
and

FIG. 7B schematically illustrates representative
circuitry for implementing the application shown in FIG.
7A.

Detailed Description of the Preferred Embodiments

Refer first to FIGS. 1A-1B, which illustrate alternative embodiments of microencapsulated electrophoretic display arrangements in accordance with the present invention. In 5 FIG. 1A, a display 120 includes a pair of planar electrodes 125, 130 which reside on opposite sides of a substantially planar arrangement of microscopic containers, or microcapsules, 133. At least electrode 133 is visually transparent so that a viewer may observe the color exhibited 10 by portions of the microcapsules 133 adjacent to electrode 130. For example, electrode 130 may comprise a semiconductor such as indium tin oxide evaporated or otherwise coated in a thin layer onto glass, mylar or other transparent substrate; the details of fabrication are well known to those skilled in 15 the art, as are possible semiconductor alternatives to indium tin oxide (see, e.g., U.S. Patent Nos. 3,668,106 and 4,305,807, the entire disclosures of which are hereby incorporated by reference).

Within each microcapsule 133 is an electrophoretic 20 suspension comprising a dielectric liquid 135 and a quantity of charged particles 137, the bulk liquid and the particles contrasting visually (i.e., exhibiting observably distinguishable colors or shades). A driver circuit 140 is electrically connected to electrodes 125, 130 and is capable 25 of creating a sufficient potential difference between the electrodes to cause migration of particles 137 to one or the other electrode within an acceptable switching time.

To impart the color of particles 137 to the display 120, driver circuit 140 creates an electric field (indicated by 30 arrows 142) whose direction is such that particles 137 are attracted to, and migrate toward, electrode 130. In the illustrated embodiment, microcapsules 133 are spherical and substantially tangent to one another; accordingly, if each

-7-

microcapsule 133 contains a quantity of particles 137 sufficient to cover half the inner surface area under the influence of an electric field, attraction of particles 137 toward electrode 130 will impart the color of the particles to display 120 in a substantially uniform, uninterrupted manner.

Microcapsules 133 need not be strictly spherical, but preferably have dimensions ranging from 5 to 500 μm , and ideally from 25 to 250 μm . The walls of microcapsules 133 should exhibit a resistivity similar to that of dielectric liquid 135. It may also be useful to match the refractive index of the microcapsules 133 with that of the electrophoretic composition. Ordinarily, liquid 135 is hydrophobic, and techniques for encapsulating a hydrophobic internal phase are well characterized in the art. The process selected may impose limitations on the identity and properties of the dielectric liquid; for example, certain condensation processes may require dielectric liquids with relatively high boiling points and low vapor pressures.

In one approach, known as "coacervation," an oil/water emulsion is formed by dispersing the electrophoretic composition (i.e., the hydrophobic dielectric liquid containing a suspension of the pigment particles 137) in an aqueous environment. One or more colloids are coacervated (i.e., agglomerated) out of the aqueous phase and deposited as shells around the oily droplets through control of temperature, pH and/or relative concentrations, thereby creating the microcapsule. Materials suitable for coacervation include gelatins and gum arabic. See, e.g., U.S. Patent No. 2,800,457 (the entire disclosure of which is hereby incorporated by reference).

The "interfacial polymerization" approach relies on the presence of an oil-soluble monomer in the electrophoretic composition, which once again is present as an emulsion in an

aqueous phase. The monomers in the minute hydrophobic droplets react with a monomer introduced into the aqueous phase, polymerizing at the interface between the droplets and the surrounding aqueous medium and forming shells around the droplets. Although the resulting walls are relatively thin and may be permeable, this process does not require the elevated temperatures characteristic of some other processes, and therefore affords greater flexibility in terms of choosing the dielectric liquid.

Our preferred microencapsulation technique is "in-situ polymerization," in which the monomers that will form the microcapsule shell are present in the aqueous phase rather than within the dispersed-phase droplets. The monomers polymerize to form a polymer with higher affinity for the internal phase than for the aqueous phase, thus condensing around the droplets as a skin. In one especially useful in-situ polymerization processes, urea and formaldehyde condense in the presence of poly(acrylic acid); see U.S. Patent No. 4,001,140. In other useful process, described in U.S. Patent No. 4,273,672, any of a variety of cross-linking agents borne in aqueous solution is deposited around microscopic oil droplets. Such cross-linking agents include formaldehyde, glyoxal, glutaraldehyde and other formaldehyde donors, trioxane, ethanolamine, ethylenediamine, boric acid, borates such as sodium borate, or macromolecular species such as gelatin, gum tragacanth, methylcellulose and A-stage formaldehyde condensation products. The entire disclosures of the '140 and '672 patents are hereby incorporated by reference.

Other useful techniques for creating microcapsules include mechanical methods, as are well known to those skilled in the art and described, for example, in U.S. Patent No. 3,585,381.

-9-

A wide range of dielectric liquids may be used with the present invention; the criteria involved in their choice includes viscosity, dielectric constant, acquired charge and density. Preferred liquids include darkly colored hydrophobic fluids, such as isoparaffinic petroleum solvent or trichlorotrifluoroethane, or a mixture thereof; and other halogenated hydrocarbons, since these tend to exhibit desirably high densities (to match that of the dispersed particles) while having desirable electrical characteristics. To further darken or impart a specific color to the liquid, a dye (e.g., an oil dye such as Oil Blue N) or other colorant (e.g., cobalt naphthenate for a violet color, manganese naphthenate for a brown color, or nickel naphthenate for a green color) can be added thereto.

A wide range of pigment particles are also useful, the primary criteria governing their choice being appropriate charge, size and color. The particles can range in size from 100 μm to less than 1 μm , but a preferred size range is 5-25 μm . The particles may exhibit a native charge, or be charged explicitly using a charge-control agent, or may acquire a charge when suspended in the dielectric liquid. Useful particulate materials include titanium dioxide (TiO_2), which provides a high-reflectance white appearance; acetylene black or other black electrophotographic toner particles; other inorganic pigments; or organic pigments such as azo and phthalocyanine materials. Typically, a charge-control agent is added to the pigment particles to confer a surface charge (zeta potential). The charge-control agent may be capable of adsorbing directly onto the particle surfaces, or mixed in during fabrication of the particles. Generally, the charge-control agent confers a zeta potential equal to 50-100 elementary charges on the surface of a particle 1 μm in radius; this produces a sufficient electrophoretic mobility on the order of 10^{-4} to 10^{-5} $\text{cm}^2/\text{V-sec}$. Suitable charge-control

-10-

agents are well known in the art; they may be polymeric or non-polymeric in nature, and may also be ionic or non-ionic. Non-ionic polymeric charge-control agents include polyethylene, polybutene succinimide and various polyvinyl pyridine block copolymers. See, e.g., U.S. Patent Nos. 5,380,362, 5,066,559 and 4,298,448, the entire disclosures of which are hereby incorporated by reference. The charge-control agent (and any underlying coating) should not interfere with the optical properties of the pigment particles. In a preferred embodiment, a mixture of TiO_2 particles and polyethylene is atomized to produce electrophoretic spheres that are largely polyethylene.

The display 120 may be formed, for example, in the manner of fabricating liquid-crystal displays. For example, after their formation, microcapsules 133 containing the electrophoretic composition may be injected into a cell housing two spaced-apart electrodes. Alternatively, microcapsules 130 may be "printed" into a display by any of various methods known in the art, e.g., the techniques used to deposit pressure-rupturable microcapsules onto a substrate to create carbonless copy paper; in this case, the particles are printed onto one of the electrodes 125, 130, after which the other electrode is deposited, printed, or otherwise coated on top of the deposited microcapsules 130.

In an alternative embodiment 145, illustrated in FIG. 1B, microcapsules 133 are immobilized within a transparent matrix or binder 150 that is itself sandwiched between electrodes 125, 130. Once again, application of the appropriately directed electric field results in migration of particles 137 toward transparent electrode 130. So long as microcapsules 133 are dispersed within matrix 150 uniformly and at sufficient density, the resulting visual appearance will be uniform. Matrix 150 is preferably a transparent polymeric material that may be cured (i.e., cross-linked from a low-viscosity state into extremely high viscosity) or otherwise

-11-

solidified at relatively low temperatures, and which readily accepts, in its low-viscosity state, a dispersion of microcapsules. Useful materials include polyvinyl alcohols, gelatins, epoxies and other resins.

5 The low-viscosity polymer precursor, into which microcapsules 133 have been suspended at an adequate dispersion density, may be cured in a mold conforming to the two-dimensional or curved shape of electrodes 125, 130, or may instead utilize the electrodes as containment boundaries for
10 an in-situ cure.

Alternatively, microcapsules 133 can be voids or microscopic cavities in matrix 150 formed during its cure. For example, the electrophoretic composition can be dispersed as an emulsion in the uncured (low-viscosity) precursor to
15 matrix 150; curing of the precursor leaves the emulsion droplets suspended and immobilized within the matrix, effectively forming a polymer-dispersed electrophoretic display.

The display can be arranged in any number of
20 configurations, including a unitary, continuous display (i.e., a contiguous extent of microcapsules sandwiched between a single electrode pair); a row or other pattern of discrete groups of microcapsules controlled by a single electrode pair; or multiple-element arrangements containing a plurality of
25 independently addressable display elements, each controlled by a separate electrode pair and comprising, for example, a single continuous display or a pattern of microcapsule groups. Driver 140 can be any suitable power supply, e.g., a DC or pulsed DC circuit, or an AC circuit (where the pulse width or
30 AC period is greater than the switching time of the electrophoretic composition).

In accordance with another aspect of the invention, however, driver 140 comprises a piezoelectric element. Refer

-12-

to FIG. 2A, which illustrates the manner in which such an element can be used to drive an electrophoretic display element 200, which comprises one or more individual electrophoretic displays. Physical deformation of the piezoelectric element 202 generates a voltage and current. The electrical output of element 202 may, if appropriate, be supplied directly to display 200; however, it is generally ~~useful to condition the output first. For example, opposite~~ deformations of element 202 produce voltages of opposite polarity; if element 202 is alternately deformed at a rate faster than the switching time of display 200, the display 200 will not respond. A voltage-conditioning circuit 204 may limit or augment the voltage produced by piezoelectric element 202, and may also include a smoothing filter to reduce variation in the voltage output or dampen the response of display 200. In operation, as the piezoelectric element is flexed in different directions, the electric field it produces changes in polarity, causing the charged particles in the electrophoretic display 200 to migrate away from one electrode and toward the other.

It should be stressed that display element 200 is not limited to the electrophoretic displays shown in FIGS. 1A-1B; the approach illustrated in FIG. 2A is applicable to any nonemissive display (e.g., liquid-crystal or electrophoretic displays), regardless of particular features, whose response characteristics are suited to the output of element 202.

A more elaborate arrangement is shown in FIG. 2A. Here, the output of conditioning circuitry 204 is provided as a power supply to a processor 206, and reaches display element via one or more switches 208 controlled by processor 206. Voltage conditioner 204 therefore rectifies and limits the magnitude of the voltage reaching processor 206, which may itself be a programmable, single-chip microprocessor or other suitable circuitry for implementing a control function. Switches 208 may be transistors, the number of which depends

-13-

on the number of individual electrophoretic display components in element 200. For example, processor 206 can be configured to close one of the switches 208—and thereby provide power to one of the components of display element 200—upon detection
5 of some external condition or at a predetermined time.

Refer now to FIG. 3, which illustrates a particular application of the invention integrated within an article of footwear apparel 300, such as a shoe. The article 300 includes a bottom portion or sole 302. Disposed within sole
10 302 is a flexible piezoelectric element 305, e.g., a sheet of polyvinylidene difluoride. The two outputs 307a, 307b are connected to the electrodes of a first electrophoretic display 310, and in the opposite sense to the electrodes of a second electrophoretic display 312. As the wearer of article 300
15 takes a step, s/he flexes piezoelectric element 305, producing a voltage of a first polarity sufficient to activate one of the displays 310, 312 (i.e., attract the particles to the visible electrode) and deactivate the other display (i.e., draw the particles away from the visible electrode). As the
20 user completes a step, piezoelectric element 305 flattens, producing a voltage of opposite polarity and reversing the respective visual appearances of displays 310, 312. The switching time of the displays is faster than the rate of a normal gait. Again, the configuration shown in FIG. 3 can
25 include voltage-conditioning circuitry if needed.

FIG. 4A illustrates another application of the invention in the environment of footwear apparel, in this case a pedometer. An article of footwear 400, such as a running shoe, includes a bottom portion or sole 402 associated with a
30 piezoelectric element 405. The outputs of piezoelectric element 405 are connected to a control circuit, described below, that governs the operation of a series of individual electrophoretic displays 412a-g. The number of such displays "turned on" (or "turned off") at any time reflects the number
35 of deformations of piezoelectric element 405 and, hence, the

number of steps taken. As shown in FIG. 4B, a suitable circuit 410 includes a full-wave rectifier or bridge 415, the rectified output of which is provided to a capacitor 417 connected in parallel with electrophoretic displays 412a-g. Each display is also connected to a respective diode 420a-g. The diodes 420a-g in the series have increasingly greater breakdown voltages. In operation, all of the electrophoretic displays are initially in the same state. Regular flexing and straightening of piezoelectric element 405 results in an approximately AC voltage output, which is rectified by bridge 415. Each pulse from bridge 415 adds charge onto the plates of capacitor 417, increasing the voltage across the capacitor and, hence, across the diode/display pairs. Each of the displays 412a-g changes state only when the accumulated charge on capacitor 417 exceeds the breakdown voltage of the associated diode. The charge on capacitor 417, of course, reflects the number of steps taken, which therefore determines the number of displays 412a-g that will have changed state. To reset the device, the user activates a switch (not shown) which reverses the connection of capacitor 417 across the diode/display pairs, bypassing the diodes and resetting the displays, and subsequently discharging capacitor 417. The circuit may also include an additional diode or other means for reducing or eliminating the high voltages caused by rapid foot travel, and means for programming the length of the user's stride so that the display reflects distance instead of steps taken.

FIG. 5 illustrates the manner in which the invention can be applied to a paper substrate, such as a book, periodical or greeting card. In the depicted embodiment, a greeting card 500 comprises a central fold 502 and a piezoelectric element 505 disposed thereon. Piezoelectric element 505 is connected (e.g., via a pair of foil traces or other conductors) to a driver circuit 507, which is itself connected to a series of three electrophoretic displays 510a, 510b, 510c via an

-15-

associated, user-actuable switch 512a, 512b, 512c. Each of displays 510a, 510b, 510c may spell out, for example, a different message. Circuit 507 includes a capacitive storage device that accumulates charge from the current produced by the user's opening of card 500, which deforms piezoelectric element 505. The stored charge is transferred to one of the displays 510a, 510b, 510c through the user's selection of the appropriate switch. A similar arrangement can be used in conjunction with a book or periodical.

10 The piezoelectric element powering an electrophoretic display need not be activated by direct deformation. Instead, it can be driven by acoustic coupling to another piezoelectric element that is itself subjected to a varying electric field (causing it to deform in proportion to the magnitude of the applied field). Such coupling can conveniently take place on length scales of 5 inches or less for typical piezoelectric displays.

Refer to FIG. 6A, which shows how this effect can be exploited in the context of a wristwatch 600. Inside the watch case 602 is a piezoelectric element 604 and an oscillator circuit 606; both of these components may be associated with the timekeeping function of watch 600. The oscillator 606 receives power from an autonomous source (e.g., a battery, not shown) and applies an AC current to piezoelectric element 604. Attached to (or embedded within) the watch band 610 is a second piezoelectric element 612 acoustically coupled to piezoelectric element 604. The outputs of element 612 are provided to a driver circuit 616, which utilizes electrical energy from element 612 to power an electrophoretic display 616. With this simple arrangement, the display 616 would constantly be "turned on."

For this reason, driver circuits 606 and 614 are preferably somewhat more sophisticated, as illustrated in FIG. 6B. Driver 606 is capable of oscillation at two or more

-16-

frequencies f_1 , f_2 . Driver circuit 614 includes a pair of notch or bandpass filters 620, 622 each tuned to a different one of the frequencies f_1 , f_2 . That is, each of filters 620 operates within a very narrow frequency band, dropping (or
5 passing) one of the frequencies f_1 , f_2 without affecting other frequencies. The outputs of filters 620, 622 are oppositely connected to display 616; the filters also contain rectifiers ~~so that their outputs to display 616 do not vary in polarity,~~ and any other conditioning circuitry desired for the
10 particular application.

Suppose, for example, that filter 620 drops frequency f_1 and filter 622 drops frequency f_2 . Operation of driver 606 at f_1 acoustically couples piezoelectric elements 604 and 612; however, electrical energy from piezoelectric element 612
15 reach display 616 only through filter 622, placing display 616 in a particular visual state. Operation of driver 606 at f_2 reverses the effect produced by filter 622, placing display 616 in the opposite state, since electrical energy passes only through filter 620. The foregoing circuit is useful, for
20 example, in setting and resetting a visual alarm.

The approach of using filters and a single driven "transmitter" piezoelectric element capable of being driven at different frequencies and, therefore, selectably coupled acoustically to multiple "receiver" elements finds application
25 in a wide variety of applications. For example, returning to the embodiment illustrated in FIG. 5, a periodical displayed at a newsstand or an advertising installation might contain several electrophoretic displays, each connected to a piezoelectric element via a differently tuned filter. By
30 altering the frequency at which the transmitter element is driven, it is possible to cycle through the various displays in any desired pattern.

The foregoing approach can also be applied, for example, to a pager or other messaging device having a piezoelectric

-17-

speaker. As shown in FIG. 7, such a device 700 includes an autonomously powered driver circuit 702 that activates a piezoelectric speaker 704 upon receiving a broadcast radio signal from a central station. Such devices are widely used and commonly available. To this device is added a second piezoelectric element 706 acoustically coupled to speaker 704; driver circuitry 708 as discussed previously; and an electrophoretic display 710. When speaker 704 produces its audible alarm, piezoelectric element 706 causes display 710 to change state, thereby providing a visual alarm indication. The display 710 can be used to convey other useful information to the user of a watch, pager, cellular telephone or other portable electronic device (e.g., the status of the battery).

It will therefore be seen that the foregoing represents a reliable and highly flexible approach to the fabrication and powering of electrophoretic and other nonemissive displays. The terms and expressions employed herein are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the invention claimed.

CLAIMS

- 1 1. An electrophoretic display comprising:
 - 2 a. an arrangement of discrete microscopic containers,
 - 3 each container being no longer than 500 μm along any
 - 4 dimension thereof;
 - 5 b. first and second electrodes disposed on and covering
 - 6 opposite sides of the arrangement, at least one of the
 - 7 electrodes being substantially visually transparent;
 - 8 c. means for creating a potential difference between the
 - 9 two electrodes; and
 - 10 d. within each container, a dielectric fluid and a
 - 11 suspension therein of particles exhibiting surface
 - 12 charges, the fluid and the particles contrasting
 - 13 visually, the potential difference causing the
 - 14 particles to migrate toward one of the electrodes.
- 1 2. The display of claim 1 wherein each container is no longer
- 2 than 5 μm along any dimension thereof.
- 1 3. The display of claim 1 wherein each container has an
- 2 average dimension ranging from 25 to 250 μm .
- 1 4. The display of claim 1 wherein the particles have average
- 2 diameters no greater than 100 μm .
- 1 5. The display of claim 1 wherein the particles have average
- 2 diameters ranging from 5 to 25 μm .
- 1 6. The display of claim 1 wherein the fluid has a fluid
- 2 density and the particles each have a particle density, the
- 3 fluid and particle densities being substantially equal.

1 7. The display of claim 1 wherein the particles comprise TiO_2
2 and the dielectric fluid comprises a darkly colored dye
3 therein.

1 8. The display of claim 1 wherein the dielectric fluid
2 comprises at least one of (i) isoparaffinic petroleum solvent
3 and (ii) trichlorotrifluoroethane.

1 9. The display of claim 7 wherein the particles each comprise
2 a core and, bound thereto, a charge-control additive.

1 10. The display of claim 1 wherein the containers have
2 interior surfaces exhibiting a resistivity, the fluid
3 exhibiting a resistivity substantially equal to the
4 resistivities of the interior surfaces.

1 11. The display of claim 1 wherein the containers are in
2 contact with one another in an array.

1 12. The display of claim 1 wherein the containers are
2 dispersed in a solid matrix.

1 13. The display of claim 1 wherein the containers are cavities
2 in a solid matrix.

1 14. The display of claim 1 wherein the means for creating a
2 potential difference comprises a piezoelectric element.

1 15. A nonemissive display system comprising:
2 a. a pair of oppositely disposed electrodes and, located
3 therebetween, at least one display element, the display
4 element being visually responsive to a potential
5 difference between the electrodes; and

-20-

6 b. a display piezoelectric element connected to the
7 electrodes, deformation of the piezoelectric element
8 producing the potential difference.

1 16. The display system of claim 15 comprising first and second
2 display elements oppositely connected to the piezoelectric
3 element, deformation of the piezoelectric element producing
4 opposite visual responses in the first and second display
5 elements.

1 17. The display system of claim 15 wherein the display
2 piezoelectric element comprises a planar sheet of
3 polyvinylidene difluoride.

1 18. The display system of claim 16 further comprising a
2 housing defining a foot enclosure including, the piezoelectric
3 element being associated with the foot enclosure such that
4 flexion thereof produces the potential difference.

1 19. The display system of claim 15 comprising a plurality of
2 selectably actuable display elements, and further comprising:
3 a. a housing defining a foot enclosure including a sole,
4 the piezoelectric element being associated with the
5 enclosure such that flexion thereof produces the
6 potential difference; and
7 b. means, connected to the piezoelectric element, for
8 selectably coupling the display elements to the
9 piezoelectric element based on a count of flexions and
10 in a pattern representative of the count.

1 20. The display system of claim 15 comprising a plurality of
2 display elements and means for selectably connecting at least
3 one display element to the piezoelectric element, deformation
4 of the piezoelectric element producing the visual responses in
5 the at least one display element connected thereto.

-21-

1 21. The display system of claim 15 further comprising:
2 a. a driver piezoelectric element acoustically coupled to
3 the display piezoelectric element;
4 b. means for applying an AC voltage to the driver element
5 at a driver frequency so as to cause the display
6 piezoelectric element to produce an AC voltage;
7 c. means for rectifying the AC voltage from the display
8 ~~piezoelectric element, the rectified voltage providing~~
9 the potential difference.

1 22. The display system of claim 15 further comprising:
2 a. a driver piezoelectric element acoustically coupled to
3 the display piezoelectric element;
4 b. means for applying an AC voltage to the driver element
5 at a driver frequency so as to cause the display
6 piezoelectric element to produce an AC voltage, the AC
7 voltage providing the potential difference;
8 c. at least one filter intervening between the display
9 piezoelectric element and the electrodes, the at least
10 one filter configured to (i) pass AC within a
11 predetermined frequency band so that the display is
12 unaffected by driver frequencies outside the
13 predetermined band, or (ii) drop AC within a
14 predetermined frequency band so that the display is
15 affected only by driver frequencies outside the
16 predetermined band; and
17 d. means, connected to the display piezoelectric element,
18 for rectifying the AC voltage from the filter and
19 thereby providing the potential difference.

1 23. The display system of claim 22 wherein the at least one
2 filter is a bandpass filter or a notch filter.

1 24. The display system of claim 22 comprising first and second
2 filters arranged in parallel and oppositely connected to the
3 display element, the first filter passing or dropping AC

-22-

4 within a first frequency band and the second filter passing or
5 dropping AC within a second frequency band, selective
6 application to the display piezoelectric element of AC within
7 the first and second frequencies producing opposite visual
8 responses from the display.

1 25. The display system of claim 24 wherein the first and
2 second filters are bandpass or notch filters.

1 26. The display system of claim 15 wherein the display element
2 comprises:

- 3 a. a substantially two-dimensional arrangement of
4 discrete microscopic containers, each container being
5 no longer than 500 μm along any dimension thereof; and
6 b. within each container, a dielectric fluid and a
7 suspension therein of particles exhibiting surface
8 charges, the fluid and the particles contrasting
9 visually, the potential difference causing the
10 particles to migrate toward one of the electrodes.

1 27. The display system of claim 22 further comprising:

- 2 a. a watch case for containing the driver piezoelectric
3 element; and
4 b. a watch band, attached to the watch case, for bearing
5 the display piezoelectric element.




FIG. 1A




FIG. 1B

2/5




FIG. 2A




FIG. 2B

3/5




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 7




FIG. 6A




FIG. 6B



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G02F 1/167, 1/133, G08B 5/22, G04C 1/00, A43B 3/00	A3	(11) International Publication Number: WO 98/19208 (43) International Publication Date: 7 May 1998 (07.05.98)
--	----	--

(21) International Application Number: PCT/US97/18643
(22) International Filing Date: 17 October 1997 (17.10.97)
(30) Priority Data:
08/738,260 25 October 1996 (25.10.96) US

(71) Applicant: MASSACHUSETTS INSTITUTE OF TECHNOLOGY [US/US]; 77 Massachusetts Avenue, Cambridge, MA 02139 (US).

(72) Inventors: JACOBSON, Joseph, M.; Apartment 1, 31 Linnaean Street, Cambridge, MA 02138 (US). COMISKEY, Barrett; 50 Massachusetts Avenue, Cambridge, MA 02139 (US).

(74) Agents: FRANK, Steven, J. et al.; Cesari and McKenna, LLP, 30 Rowes Wharf, Boston, MA 02110 (US).

(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, HU, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(88) Date of publication of the international search report: 9 July 1998 (09.07.98)

(54) Title: NONEMISSIVE DISPLAYS AND PIEZOELECTRIC POWER SUPPLIES THEREFOR

**(57) Abstract**

An electrophoretic display has a substantially two-dimensional arrangement of microcapsules each having therein an electrophoretic composition of a dielectric fluid and a suspension of particles that visually contrast with the dielectric liquid and also exhibit surface charges; a pair of electrodes, at least one of which is visually transparent, disposed on and covering opposite sides of the microcapsule arrangement; and means for creating a potential difference between the two electrodes, the potential difference causing the particles to migrate toward one of the electrodes. The display may be powered by one or more piezoelectric elements, which are also suitable for powering other types of nonemissive displays.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

Internatic Application No

PCT/US 97/18643

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G02F1/167 G02F1/133 G08B5/22 G04C1/00 A43B3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 1 314 906 A (MATSUSHITA) 26 April 1973	1,3-11, 13
Y	see page 8, line 41 - line 72; figure 8C see page 9, line 121 - line 124 see page 10, line 111 - page 11, column 10; figure 12A	2,12,14
X	--- PATENT ABSTRACTS OF JAPAN vol. 13, no. 454 (P-944) & JP 01 177517 A (KINSEKI), 13 July 1989, see abstract	1
X	--- SANKUS. J: "Electrophoretic display cell." XEROX DISCLOSURE JOURNAL., vol. 4, no. 3, 1979, STAMFORD, CONN US, page 309 XP002052704 see the whole document ---	1
-/--		

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

21 April 1998

Date of mailing of the international search report

20.05.98

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Diot, P

INTERNATIONAL SEARCH REPORT

Internat. Application No

PCT/US 97/18643

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 622 721 A (ADVANCED MICRO DEVICES) 2 November 1994	14
X	see column 2, line 05 - line 25 see column 7, line 57 - column 8, line 13 ---	15
Y	US 4 919 521 A (TADA) 24 April 1990 see column 1, line 51 - column 2, line 64 see column 3, line 68 - column 4, line 02 ---	2,12
X	US 5 500 635 A (MOTT) 19 March 1996 see column 10, line 36 - line 67; figure 7 see column 15, line 47 - column 17, line 07 see column 13, line 65 - column 14, line 34 ---	15-20
A	US 4 185 621 A (MORROW) 29 January 1980 see column 6, line 13 - column 27 -----	15,21

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 97/ 18643

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. CLAIMS: 01-14
2. CLAIMS: 15-27

FOR FURTHER INFORMATION PLEASE SEE FORM PCT/ISA/206 MAILED: 09.02.98.

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat. Application No

PCT/US 97/18643

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 1314906	A	26-04-1973	DE 2029463 A	25-02-1971
			FR 2051099 A	02-04-1971
			NL 7008551 A,B	15-12-1970

EP 622721	A	02-11-1994	US 5548764 A	20-08-1996
			JP 6332383 A	02-12-1994

US 4919521	A	24-04-1990	JP 63303325 A	09-12-1988
			JP 1038732 A	09-02-1989
			JP 1057242 A	03-03-1989
			JP 1126629 A	18-05-1989



US 5500635	A	19-03-1996	AT 123563 T	15-06-1995
			AU 7340191 A	18-09-1991
			CA 2073691 A	21-08-1991
			DE 69110277 D	13-07-1995
			DE 69110277 T	19-10-1995
			EP 0516703 A	09-12-1992
			WO 9113288 A	05-09-1991
			JP 5504283 T	08-07-1993
			AU 1956492 A	14-01-1993
			CA 2073586 A	13-01-1993
			EP 0522882 A	13-01-1993
			JP 5228002 A	07-09-1993
			KR 9611268 B	21-08-1996

US 4185621	A	29-01-1980	NONE	

XP-002052704

ELECTROPHORETIC DISPLAY CELL
Joseph Sankus

Proposed Classification
U.S. Cl. 294/299
Int. Cl. B01d 13/02



An electrophoretic device which will inhibit settlement of large pigment agglomerates after a period of time due to the force of gravity. The device comprises a multi-cell construction positioned between two spaced electrodes, a transparent viewing electrode 1 and a rear electrode 2. Each cell 3 is in the shape of a funnel including a flared lead portion 4 facing the viewing electrode 1 and a narrow, tubular rear portion 5 terminating at the rear electrode 2. Attached to the viewing electrode 1 and associated with each cell 3 is a small opaque or highly reflective dot 6 having the exact diameter and being coaxial with the tubular portion 5. The cells are filled with a dye and pigment particle solution 7.

When a cell is "OFF", the pigment resides in the tubular rear portion 5 and is hidden from view by the dot 6. When the cell is addressed and turned "ON", the particles migrate toward the viewing electrode 1 into the flared portion 4 of the cell, thus causing that cell to be visibly darker.